

BATTERY-BOX PREMIUM HVS / HVM

- Capable of High-Powered Emergency-Backup and Off-Grid Functionality
- Highest Efficiency Thanks to a Real High-Voltage Series Connection
- The Patented Modular Plug Design Requires no Internal Wiring and Allows for Maximum Flexibility and Ease of Use
- Cobalt Free Lithium Iron Phosphate (LFP) Battery: Maximum Safety, Life Cycle, and Power
- Compatible with Leading 1 and 3 Phase High Voltage Battery Inverters
- Two Distinct Modules to Cover the Complete Range of System Sizes
- Highest Safety Standards like VDE 2510-50



BATTERY-BOX PREMIUM HVS

One Battery-Box Premium HVS is composed of 2 to 5 HVS battery modules that are connected in series to achieve a usable capacity of 5.1 to 12.8 kWh.

Additionally, direct parallel connection of up to 3 identical Battery-Box Premium HVS allows a maximum capacity of 38.4 kWh.

Ability to scale by adding HVS modules or parallel HVS stacks later.




BATTERY-BOX PREMIUM HVM

One Battery-Box Premium HVM is composed of 3 to 8 HVM battery modules that are connected in series to achieve a usable capacity of 8.3 to 22.1 kWh.

Additionally, direct parallel connection of up to 3 identical Battery-Box Premium HVM allows a maximum capacity of 66.2 kWh.

Ability to scale by adding HVM modules or parallel HVM stacks later.




FLEXIBLE, EFFICIENT, SIMPLE



Internal Plug Connection
No Additional Wiring Required



5.1 - 66.2 kWh
Tailored Sizing for Each Application













Extend Anytime
Easily Adapts to New Requirements



High Power
Power for Every Application

TECHNICAL PARAMETERS PREMIUM HVS / HVM

	 HVS 5.1	 HVS 7.7	 HVS 10.2	 HVS 12.8
Battery Module	HVS (2.56 kWh, 102.4 V, 38 kg)			
Number of Modules	2	3	4	5
Usable Energy [1]	5.12 kWh	7.68 kWh	10.24 kWh	12.8 kWh
Max Output Current [2]	25 A	25 A	25 A	25 A
Peak Output Current [2]	50 A, 5 s	50 A, 5 s	50 A, 5 s	50 A, 5 s
Nominal Voltage	204 V	307 V	409 V	512 V
Operating Voltage	160~230 V	240~345 V	320~460 V	400~576 V
Dimensions (H/W/D)	712x585x298 mm	945x585x298 mm	1178x585x298 mm	1411x585x298 mm
Weight	91 kg	129 kg	167 kg	205 kg

	 HVM 8.3	 HVM 11.0	 HVM 13.8	 HVM 16.6	 HVM 19.3	 HVM 22.1
Battery Module	HVM (2.76 kWh, 51.2 V, 38 kg)					
Number of Modules	3	4	5	6	7	8
Usable Energy [1]	8.28 kWh	11.04 kWh	13.80 kWh	16.56 kWh	19.32 kWh	22.08 kWh
Max Output Current [2]	50 A	50 A	50 A	50 A	50 A	50 A
Peak Output Current [2]	75 A, 5 s	75 A, 5 s	75 A, 5 s	75 A, 5 s	75 A, 5 s	75 A, 5 s
Nominal Voltage	153 V	204 V	256 V	307 V	358 V	409 V
Operating Voltage	120~173 V	160~230 V	200~288 V	240~345 V	280~403 V	320~460 V
Dimensions (H/W/D)	945 x 585 x 298 mm	1178 x 585 x 298 mm	1411 x 585 x 298 mm	1644 x 585 x 298 mm	1877 x 585 x 298 mm	2110 x 585 x 298 mm
Weight	129 kg	167 kg	205 kg	243 kg	281 kg	319 kg

HVS & HVM

Operating Temperature	-10 °C to +50°C
Battery Cell Technology	Lithium Iron Phosphate (cobalt-free)
Communication	CAN/RS485
Enclosure Protection Rating	IP55
Round-trip Efficiency	≥96%
Certification	VDE2510-50 / IEC62619 / CEC / CE / UN38.3
Applications	ON Grid / ON Grid + Backup / OFF Grid
Warranty [3]	10 Years
Compatible Inverters	Refer to BYD Battery-Box Premium HVS / HVM Compatible Inverter List

[1] DC Usable Energy, Test conditions: 100% DOD, 0.2C charge & discharge at + 25 °C. System Usable Energy may vary with different inverter brands

[2] Charge derating will occur between -10 °C and +5 °C

[3] Conditions apply. Refer to BYD Battery-Box Premium Limited Warranty Letter.



BATTERY-BOX PREMIUM LVL

- Scalable from 15.4 to 983 kWh
- Compatible with 1 and 3 Phase Inverters
- Cobalt Free Lithium Iron Phosphate (LFP) Battery: Maximum Safety, Life Cycle, and Power
- Capable of High-Powered Back-up and Off-Grid Function
- Space Saving via the Ability to Stack 2 Premium Batteries
- Add Additional Batteries in Parallel to Expand the System



BATTERY-BOX PREMIUM LVL

The BYD Battery-Box Premium LVL is a lithium iron phosphate (LFP) battery for use with an external inverter.

Thanks to its control and communication unit (BMU), the Battery-Box Premium LVL scales to meet the project requirements, no matter how large they may be. Start with Battery-Box Premium LVL15.4 (15.36 kWh) and extend later to 983 kWh using parallel interconnection of up to 64 batteries.



FLEXIBLE, EFFICIENT, SIMPLE



Easy Installation
With Easy Transportation



15.4 - 983 kWh
Tailored Sizing for Each Application



Extend Anytime
Easily Adapts to New Requirements



High Power
Power for Every Application

TECHNICAL PARAMETERS **PREMIUM LVL**



LVL15.4

Number of Modules	2
Usable Energy [1]	15.36 kWh
Max Cont. Output Current [2]	250 A
Peak Output Current [2]	375 A, 5 s
Dimensions (H/W/D)	500 x 575 x 650 mm
Weight	164 kg
Nominal Voltage	51.2 V
Operating Voltage	40-59 V
Operating Temperature	-10 °C to +50°C
Battery Cell Technology	Lithium Iron Phosphate (cobalt-free)
Communication	CAN/RS485
Enclosure Protection Rating	IP20
Round-trip Efficiency	≥95%
Scalability	Max. 64 in Parallel (983 kWh)
Certification	IEC62619 / CE / CEC / UN38.3
Applications	ON Grid / ON Grid + Backup / OFF Grid
Warranty [3]	10 Years
Compatible Inverters	Refer to BYD Battery-Box Premium LVL Minimum Configuration List

[1] DC Usable Energy, Test conditions: 100% DOD, 0.2C charge & discharge at + 25 °C. System Usable Energy may vary with different inverter brands

[2] Charge derating will occur between -10 °C and +5 °C

[3] Conditions apply. Refer to BYD Battery-Box Premium Limited Warranty Letter.



BATTERY-BOX PREMIUM LVS

- Scalable from 4 kWh to 256 kWh
- Maximum Flexibility for any Application with up to 64 Modules Connected in Parallel
- Compatible with Market Leading 1 and 3 Phase Inverters
- Cobalt Free Lithium Iron Phosphate (LFP) Battery: Maximum Safety, Life Cycle and Power
- Capable of High-Powered Emergency-Backup and Off-Grid Function
- Patented Internal Plug Design Requires No Additional Wiring
- Self-Consumption Optimization for Residential and Commercial Applications




BATTERY-BOX PREMIUM LVS

- 4 kWh Module
- Modular Design Simplifies Transport and Installation

The BYD Battery-Box Premium LVS is a lithium iron phosphate (LFP) battery pack for use with an external inverter. A single Battery-Box Premium LVS contains between 1 to 6 battery modules LVS stacked in parallel and can reach 4 to 24.0 kWh usable capacity in one tower:

- Battery-Box LVS 4.0 (4 kWh)
- Battery-Box LVS 8.0 (8 kWh)
- Battery-Box LVS 12.0 (12 kWh)
- Battery-Box LVS 16.0 (16 kWh)
- Battery-Box LVS 20.0 (20 kWh - single tower only)
- Battery-Box LVS 24.0 (24 kWh - single tower only)


Connect up to 16 Battery-Box LVS 16.0 in parallel for a maximum size of 256 kWh. Ability to scale by adding LVS modules or parallel towers of 1 to 4 modules later.




FLEXIBLE, EFFICIENT, SIMPLE



Internal Plug Connection
No Additional Wiring Required



4 - 256 kWh
Tailored Sizing for Each Application









Extend Anytime
Easily Adapts to New Requirements



High Power
Power for Every Application

TECHNICAL PARAMETERS PREMIUM LVS

						
	LVS 4.0	LVS 8.0	LVS 12.0	LVS 16.0	LVS 20.0	LVS 24.0
Battery Module	LVS (4 kWh, 51.2 V, 45 kg)					
Number of Modules	1	2	3	4	5	6
Usable Energy [1]	4 kWh	8 kWh	12 kWh	16 kWh	20 kWh	24 kWh
Max Cont. Output Current [2]	65 A	130 A	195 A	250 A	250 A	250 A
Peak Output Current [2]	90 A, 5 s	180 A, 5 s	270 A, 5 s	360 A, 5 s	360 A, 5 s	360 A, 5 s
Dimensions (H/W/D)	478 x 650 x 298 mm	711 x 650 x 298 mm	944 x 650 x 298 mm	1177 x 650 x 298 mm	1410 x 650 x 298 mm	1643 x 650 x 298 mm
Weight	64 kg	109 kg	154 kg	199 kg	244 kg	289 kg
Nominal Voltage	51.2 V					
Operating Voltage	40-57.6 V					
Operating Temperature	-10 °C to +50°C					
Battery Cell Technology	Lithium Iron Phosphate (cobalt-free)					
Communication	CAN / RS485					
Enclosure Protection Rating	IP55					
Round-Trip Efficiency	≥95%					
Scalability [3]	Max. 64 Modules in Parallel (256 kWh)				Single Tower Only	
Certification	VDE2510-50 / IEC62619 / CE / CEC / UN38.3					
Applications	ON Grid / ON Grid + Backup / OFF Grid					
Warranty [4]	10 Years					
Compatible Inverters	Refer to BYD Battery-Box Premium LVS Minimum Configuration List					

[1] DC Usable Energy, Test conditions: 100% DOD, 0.2C charge & discharge at + 25 °C. System Usable Energy may vary with different inverter brands

[2] Charge derating will occur between -10 °C and +5 °C

[3] Parallel tower function only available for 1 to 4 battery modules per tower. LVS 20.0 and LVS 24.0 can only be used as a single tower.

[4] Conditions apply. Refer to BYD Battery-Box Premium Limited Warranty Letter.

